


Valena™ Life Double socket outlets - Franco-Belgian standard

Cat. No(s): 7 531 86/87 - 7 532 86/87 - 7 533 86/87



1. USE

2 x 2 P+E compact socket outlets .

Mechanisms supplied complete with cover plate and plate.

Supplied with site protection cover.

Installation in 1-gang flush-mounting box, allows replacing one socket by two sockets without changing mounting box.


Flush-mounting or surface-mounting.

2. RANGE

Description	White	lvory	Aluminium
Double socket 2 x 2 P+E with shutters	7 531 86	7 532 86	7 533 86
Double socket 2 x 2 P+E without shutters	7 531 87	7 532 87	7 533 87

3. OVERALL DIMENSIONS (mm)

Cat. No: 7 531 86



A	В	С	D
114	86	43.25	19.25

4. CONNEXION

Automatic terminals Capacity: 2 x 2.5 mm² Stripping length: 13 mm Flexible or rigid cables compatible

5. TECHNICAL CHARACTERISTICS

■ 5.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 20 Protection against impact: IK 04

5.2 Material characteristics

Polygloss appearance

- Colour: White RAL 9003
 - Ivory RAL 1013
 - Aluminium
- Material: Plate ABS
 - Socket cover plate: Polycarbonate
 - Halogen free
 - UV resistant

Material of the support: - Polycarbonate grey RAL 7037 + Metal - Halogen free

Self-extinguishing:

- + 850° C / 30 s for insulating parts holding live parts in place
- + 650° C / 30 s for other parts made of insulating materials.

■ 5.3 Electrical characteristics

Voltage: 250 V~ Current:16 A Frequency: 50/60 Hz

5.4 Climatic characteristics

Storage and usage temperature: - 5° C to + 35° C

6. MAINTENANCE

Surface cleaning with a cloth. Do not use: acetone, tar remover, trichloroethylene.

Maintenance with the following products: Hexane (EN 60669-1), Methylated spirit, Soapy water, Diluted ammonia, Bleach diluted to 10%, Window-cleaning products.

Caution: A preliminary test should be carried out if other specific cleaning products are to be used.

7. STANDARDS AND APPROVALS

. 1.....

Compliance with standards of installation and manufacturing. Refer to e. catalogue.